
DEDUCTS RESOURCE

THINGS TO KNOW

The following doesn't account for every unique condition possible but does a good job of prompting questions and conversations between manufacturer, installer and property.



DUST CAP OR 1"X2" An additional 0.25" - 0.75" allowance may be needed to account for the top treatment's dust cap/roof board. Construction styles and materials vary greatly, so please be sure to confirm thickness and style prior to finalizing deduction here.



RIPPLEFOLD OR PLEATED Ripplefold draperies traverse below the hardware, requiring a 1.0" allowance for ceiling mounted 94004 track; while pinch pleated draperies hang only 0.25" below the ceiling with 94004 track. Please note decorative hardware, 94003 track and wall mount hardware all require variations based on application.



OR

CARPET OR SOLID SURFACE Assuming finished floor was not in place during measure, an additional allowance will be required. As flooring materials have increased in variability, a standard 0.25" carpet pad and 0.50" carpet deduction can no longer be assumed. LVT/VCT Flooring is also used oftentimes, with varying thickness. Be sure to confirm finished flooring allowances every time.



ABOVE FINISHED FLOOR Standard clearance above the finished floor is 0.50", however there are times where design may dictate higher (.75" – 1.5" above floor) or lower (skimming/puddling the floor). All treatments are subject to a 0.25" allowance during manufacturing, therefore, we are unable to commit to tolerances tighter than 0.50"AFF without customer accepting that treatments may also skim the floor.



NOTES, EXCEPTIONS & ASTERISKS Any treatment above 120" height should be evaluated for an increased deduction, due to weight and height. Fabric utilizing an open/loose construction should be considered for an additional deduction (0.25" - 1.0"). New construction floors are often floated (post concrete/prefinished flooring) to level the room requiring an additional allowance.

